

Q50 (V37) & Q60 (CV37) Mirror Cover Replacement & Installation Guide

1. Power on the car and aim the mirrors in-wards as far as possible, to expose this tab, visible through the gap between the mirror glass and mirror housing.



2. Using a screwdriver or plastic tool, push this tab (It will bow slightly towards the car).



3. While you push that tab, start working a thin plastic tool in between the outer housing and the frame around the mirror, starting near the end of the turn signal lens.



4. Once you open up that gap enough, use a plastic spudger to open it up more.



5. Begin prying the cover away from the housing using your plastic tool. Another set of hands helps a lot with this. You want to work the cover towards the front of the car.



6. Starting from the corner where you first got the plastic tool in, work your way around the housing to separate it.





7. As you work your way around, the mirror will try to hang on at the closest point to the car. Continue to apply force pushing the cover towards the front of the car, and avoid allowing the cover to “hinge” at this point, as that may cause damage to the clips on the original cover. If necessary, you can also fold the mirror body in to get another angle on the inner-most clip.



8. Eventually, the cover will give up. You can see the 6 clips holding it in place here. The far left on is the one we push at the very beginning of the process.



9. And here is the mirror housing without the cover.



10. Finally, just line up the clips on the new cover with the receiver holes on the body and push towards the mirror housing (applying force towards the back of the car). It will pop into place, and that's it!



www.conceptzperformance.com